


## DEDU - SCHALUNGSSPANNSTELLE

DEDU - Formwork spacer consisting of distance sleeve 22/26 and cones 22. Cones not mounted. Delivery with plugs.

Item-No.	Tube Ø mm	Wall thickness mm	Pcs/ Bag	Pcs/ Pallet
DED15	22/26	150	100	1.800
DED18	22/26	180	100	1.800
DED20	22/26	200	100	1.800
DED23	22/26	230	100	1.800
DED25	22/26	250	100	1.800
DED30	22/26	300	100	1.800
DED35	22/26	350	100	1.800
DED40	22/26	400	100	1.800
DED50	22/26	500	100	1.800
DED65	22/26	650	50	1.800



## KONUS

Item-No.	For tube Ø mm	Fitting length mm	Pcs/ Bag	Pcs/ Pallet
K22*	22	10	500	30.000

\* K22 also available in blue



Cone

## KONUS INKL. DICHTSCHEIBE

Cone for fair-faced concrete requirement incl. glued on sealing disc.

Item-No.	For tube Ø mm	Outside Ø mm	Fitting length mm	Pcs/ Box	Pcs/ Pallet
K22S	22/26	42	10	500	24.000



## DICHTSCHEIBE

EPDM sealing disc with self adhesive foil.


Item-No.	For item	Inside Ø mm	Outside Ø mm	Strength mm	Pcs/ Coil	Coil/ Box	Pcs/ Pallet
DIS43/250	K22	20	42	6	250	9	22.500
DISOP	OP22	25	42	6	250	9	22.500
DISOP26	OP26	27	45	6	250	9	22.500



## SICHTBETONKEGEL

Cone in high fair-faced concrete quality. Fits for cone K22. After removing the cone, the fair-faced concrete cone is glued into the conical opening. The result is a small shadow gap.

Item-No.	Material	Ø D1 mm	Ø D2 mm	Length mm	Pcs/ Box	Pcs/ Bag	Pcs/ Pallet
SBK22GB	concrete	38	19	26,5	100	-	4.000
*SBK22KS	plastic	37	21,6	28	-	250	5.000



## SICHTBETONKEGEL UNIVERSAL

Prefabricated cone in high-quality fair-faced concrete for closing tie holes with an inner diameter of 22 to 26 mm in combination with cones with a cover of 10 mm as well as OKTAGON-PLUS 22 or 26.

Item-No.	For tube Ø mm	Pcs/ Box	Pcs/ Pallet
SBKU2226GB	22 - 26	72	3.960

