

Double wall spacer  
RAZZO 1



## RAZZO 1

Spacer for prefabricated double walls. Efficient attachment by sliding shoe underneath the reinforcement. The spacer is in a safe position immediately.

Item-No.	Concrete cover mm	Wall thickness mm	Iron Ø mm	Pcs/Box	Pcs/Pallet
RAZ.../200	15-35	200	8 oder 10	150	3.000
RAZ.../240	15-35	240	8 oder 10	150	3.000
RAZ.../250	15-35	250	8 oder 10	150	3.000
RAZ.../300	15-35	300	8 oder 10	150	3.000
RAZ.../500	15-35	500	8 oder 10	65	1.560

Other length or wall thickness available on request.



## RAZZO 2

Small foot for close-meshed reinforcement.

Double wall spacer  
RAZZO 2



Item-No.	Concrete cover mm	Wall thickness mm	Iron Ø mm	Pcs/Box	Pcs/Pallet
RAZ08/200...2	15-30	200	8	200	4.000
RAZ08/240...2	15-30	240	8	200	4.000
RAZ08/250...2	15-30	250	8	200	4.000
RAZ08/300...2	15-30	300	8	150	3.000

Item-No.	Concrete cover mm	Wall thickness mm	Iron Ø mm	Pcs/Box	Pcs/Pallet
RAZ10/200...2	20-35	200	10	300	6.000
RAZ10/240...2	20-35	240	10	250	5.000
RAZ10/250...2	20-35	250	10	250	5.000
RAZ10/300...2	20-35	300	10	200	4.000

Other length or wall thickness available on request.



TEST CERTIFICATION ON REQUEST

## RAZZO-PLUS MIT STAHLKERN

Double wall spacer with steel core  
RAZZO-PLUS (RAZS...)



Robust spacer for prefabricated double walls. Made of special plastic in one piece with steel core. Efficient attachment by sliding shoe underneath the reinforcement. The spacer is in a safe position immediately.

Item-No.	Concrete cover mm	Wall thickness mm	Iron Ø mm	Pcs/Box	Pcs/Pallet
RAZS/160S	15-50	160	8	145	3.480
RAZS/180S	15-50	180	8	145	3.480
RAZS/200S	15-50	200	8	150	3.600
RAZS/240S	15-50	240	8	120	2.880
RAZS/250S	15-50	250	8	120	2.880
RAZS/300S	15-50	300	8	110	2.640
RAZS/350S	15-50	350	10	100	2.400
RAZS/400S	15-50	400	10	90	2.160
RAZS/500S	15-50	500	8	65	1.560

Also available RAZZO-PLUS WU (RAZS/...SQ)!



## RAZZO-PLUS WU

With active sealing ring against liquid entry. 5 Bar test pressure due to DIN EN 12390-8.