

DEDU - SCHALUNGSSPANNSTELLE

DEDU - Formwork spacer consisting of distance sleeve 22/26 and cones 22.
Cones not mounted. Delivery without plugs.

Item-No.	Tube Ø mm	Wall thickness mm	Pcs/ Bag	Pcs/ Pallet
DED15D	22/26	150	100	1.800
DED18D	22/26	180	100	1.800
DED20D	22/26	200	100	1.800
DED23D	22/26	230	100	1.800
DED25D	22/26	250	100	1.800
DED30D	22/26	300	100	1.800
DED35D	22/26	350	100	1.800
DED40D	22/26	400	100	1.800
DED50D	22/26	500	100	1.800
DED65D	22/26	650	50	1.800



KONUS

Item-No.	For tube Ø mm	Fitting length mm	Pcs/ Bag	Pcs/ Pallet
K22*	22	10	500	30.000

* K22 also available in blue




Cone

KONUS INKL. DICHTSCHEIBE

Cone for fair-faced concrete requirement incl. glued on sealing disc.

Item-No.	For tube Ø mm	Outside Ø mm	Fitting length mm	Pcs/ Box	Pcs/ Pallet
K22S	22/26	42	10	500	24.000



DICHTSCHEIBE

EPDM sealing disc with self adhesive foil.

Item-No.	For item	Inside Ø mm	Outside Ø mm	Strength mm	Pcs/ Coil	Coil/ Box	Pcs/ Pallet
DIS43/250	K22	20	42	6	250	9	22.500
DISOP	OP22	25	42	6	250	9	22.500
DISOP26	OP26	27	45	6	250	9	22.500



SICHTBETONKEGEL

Cone in high fair-faced concrete quality. Fits for cone K22. After removing the cone, the fair-faced concrete cone is glued into the conical opening. The result is a small shadow gap.

Item-No.	Material	Ø D1 mm	Ø D2 mm	Length mm	Pcs/ Box	Pcs/ Bag	Pcs/ Pallet
SBK22GB	concrete	38	19	26,5	100	-	4.000
SBK22KS	plastic	37	21,6	28	-	250	5.000

*

