

## 4-PUNKT AUFLAGE MIT FEDERBALLKLIP

Item-No.	Concrete cover mm	Pcs / Bag	Pcs / Pallett	Weight kg / Pcs	Weight kg / Pallet
GBVA15/4FTB	15	448	26.880	0,030	806
GBVA20/4FTB	20	384	23.040	0,035	806
GBVA25/4FTB	25	384	19.200	0,044	845
GBVA30/4FTB	30	320	12.800	0,056	717
GBVA35/4FTB	35	320	12.800	0,065	832
GBVA40/4FTB	40	256	10.240	0,075	768
GBVA45/4FTB	45	256	10.240	0,080	819
GBVA50/4FTB	50	192	7.680	0,092	707

Approved according to DBV specification „Abstandhalter“ DBV - c - L2/F/T/A

Cast concrete single spacer  
„FOUR FEET“ with shuttlecock clip



## 4-PUNKT AUFLAGE MIT KUNSTSTOFFKLAMMER

Item-No.	Concrete cover mm	Pcs / Bag	Pcs / Pallett	Weight kg / Pcs	Weight kg / Pallet
GBVA15/4KKTB	15	448	26.880	0,030	806
GBVA20/4KKTB	20	384	23.040	0,035	806
GBVA25/4KKTB	25	384	19.200	0,044	845
GBVA30/4KKTB	30	320	12.800	0,056	717
GBVA35/4KKTB	35	320	12.800	0,065	832
GBVA40/4KKTB	40	256	10.240	0,075	768
GBVA45/4KKTB	45	256	10.240	0,080	819
GBVA50/4KKTB	50	192	7.680	0,092	707

Approved according to DBV specification „Abstandhalter“ DBV - c - L2/F/T/A

Cast concrete single spacer  
„FOUR FEET“ with plastic clamp



## 4-PUNKT AUFLAGE MIT ÖSENDRAHT

Item-No.	Concrete cover mm	Pcs / Bag	Pcs / Pallett	Weight kg / Pcs	Weight kg / Pallet
GBVA15/4OTB	15	448	26.880	0,030	806
GBVA20/4OTB	20	384	23.040	0,035	806
GBVA25/4OTB	25	384	19.200	0,044	845
GBVA30/4OTB	30	320	12.800	0,056	717
GBVA35/4OTB	35	320	12.800	0,065	832
GBVA40/4OTB	40	256	10.240	0,075	768
GBVA45/4OTB	45	256	10.240	0,080	819
GBVA50/4OTB	50	192	7.680	0,092	707
GBVA60OTB	60	144	5.760	0,160	736

Approved according to DBV specification „Abstandhalter“ DBV - c - L2/F/T/A

Cast concrete single spacer  
„FOUR FEET“ with plastic clamp

