


S-SCHLANGE

certified type



This product has been tested and certified in accordance with the requirements of the DBV datasheet: „DBV-Merkblatt Unterstützungen“ July 2002

Wire spacer between upper and lower reinforcement mesh.

Snake form ensures high firmness and stability. No contact to formwork so no risk of corrosion.

Item No.	Hight mm	Length m	Pcs/ Bundle	Pcs/ Pallet
UK04AZ	40	2	25	2.000
UK05AZ	50	2	25	1.000
UK06AZ	60	2	25	1.000
UK07AZ	70	2	25	1.000
UK08AZ	80	2	25	1.000
UK09AZ	90	2	25	1.000
UK10AZ	100	2	25	1.000
UK11AZ	110	2	25	1.000
UK12AZ	120	2	25	1.000
UK13AZ	130	2	25	1.000
UK14AZ	140	2	25	1.000
UK15AZ	150	2	25	1.000
UK16AZ	160	2	25	1.000
UK17AZ	170	2	25	500
UK18AZ	180	2	25	500
UK19AZ	190	2	25	500
UK20AZ	200	2	25	500

Other dimensions available on request.

S-SCHLANGE - LEICHT

light-weight type



Wire spacer between upper and lower reinforcement mesh.

Snake form ensures high firmness and stability. No contact to formwork so no risk of corrosion

Item No.	Hight mm	Length m	Pcs/ Bundle	Pcs/ Pallet
UK04	40	2	25	1.800
UK05	50	2	25	1.600
UK06	60	2	25	1.400
UK07	70	2	25	1.200
UK08	80	2	25	1.000
UK09	90	2	25	1.000
UK10	100	2	25	800
UK11	110	2	25	800
UK12	120	2	25	600
UK13	130	2	25	600
UK14	140	2	25	600
UK15	150	2	25	600
UK16	160	2	25	600
UK17	170	2	25	400
UK18	180	2	25	400
UK19	190	2	25	400
UK20	200	2	25	400

Other dimensions available on request.