

DRUPAK

Large-area and very stable spacer, mainly for the lower reinforcement. Very good concrete flow through large side and top cut-outs. Only limited suitable for fair-faced concrete and precast ceilings.

Item-No.	Concrete cover mm	Length m	m/ Bundle	m/ Pallet
DP..15/200	15	2	100	6.000
DP...20/200	20	2	100	6.000
DP...25/200	25	2	100	5.400
DP...30/200	30	2	100	5.400
DP...35/200	35	2	60	4.680
DP...40/200	40	2	60	4.320
DP...50/200	50	2	60	4.320


Because of better stability we advice to use Drupak "2" for concrete cover of 35mm or higher.

Item-No.	Concrete cover mm	Length m	m/ Bundle	m/ Pallet
DPF35/200...2	35	2	60	3.900
DPF40/200...2	40	2	60	3.600
DPF45/200...2	45	2	60	3.000
DPF50/200...2	50	2	60	3.000



Approved according to DBV specification „Abstandhalter“ DBV - c - L2/F




Drupak „1“
Width 36mm



Drupak „2“
Width 46mm



DPF - flat on top:
Possible for Drupak „1“ and Drupak „2“.




DPW - wave on top:
Prevent the rebars from slipping. Only possible for Drupak „1“.

DRUPAK VOLL

Extra strong spacer with large supporting area for the lower reinforcement for soft subsoil or when using insulating materials. Very good concrete flow by large cut outs on the site and on top.

Artikel-Nr.	Beton-deckung mm	Länge cm	m/ Bund	m/ Palette
DPO40/100	40	100	36	1.728
DPO40/200	40	200	72	3.456
DPO50/100	50	100	36	1.260
DPO50/200	50	200	72	2.520



DRUWA

Large-area spacer with high stability for the lower reinforcement. Due to its zigzag shape and staggered feet, good concrete flow is ensured. By turning, the DRUWA can easily be used for soft surfaces. Due to its special design the pallets are well stack-able! Therefore optimal saving of freight costs and perfect using of storage room.

Item-No.	Concrete cover mm	Length m	Pcs/ Bundle	Pcs/ Pallet
DUW15/80	15	80	70	4.410
DUW20/80	20	80	60	3.780
DUW25/80	25	80	40	2.800
DUW30/80	30	80	40	2.520
DUW35/80	35	80	30	2.100
DUW40/80	40	80	30	1.890
DUW50/80	50	80	20	1.540

Approved according to DBV specification „Abstandhalter“ DBV - c - L2

