

DRUFILA-PLUS

Spacers for light reinforcement with very good concrete flow. Special foot spikes minimise contact with formwork.

Item-No.	Concrete cover mm	Length m	m/ Bundle	m/ Pallet
DUFPL20/100	20	1	80	3.840
DUFPL25/100	25	1	80	3.520
DUFPL30/100	30	1	80	3.200
DUFPL35/100	35	1	80	2.880
DUFPL40/100	40	1	80	2.560
DUFPL50/100	50	1	80	1.920
DUFPL60/100	60	1	80	1.920

Width 55 mm



Approved according to DBV specification „Abstandhalter“ DBV - c - L1/F/T/A



Very stable due to lateral support.

UNOCLIP

Item-No.	Concrete cover mm	For Iron Ø mm	Pcs/ Box	Pcs/ Pallet	Pcs/ Oktabin*
SCO15/6	15	6	4.000	60.000	-
SCO15/6-8	15	6-8	4.000	60.000	-
SCO20/6	20	6	2.300	34.500	25.000
SCO20/6-8	20	6-8	2.300	34.500	25.000
SCO25/6	25	6	1.500	22.500	18.000
SCO25/6-8	25	6-8	1.500	22.500	18.000
SCO30/6-8	30	6-8	1.300	19.500	13.500
SCO30/8-10	30	8-10	1.300	19.500	13.500
SCO35/6	35	6	1.000	15.000	-
SCO35/6-8	35	6-8	1.000	15.000	-

* loose in Oktabin



Iron Ø 6 mm



Iron Ø 6-8 mm



Iron Ø 8-10 mm