

Column formwork Nevotube®
„square“



SCHALROHR NEVOTUBE® “QUADRAT“

Flexibility

All dimensions from 150x150mm to 800x800mm available in 2-3 working days.
Delivery to the building site in customized length.

Quality

100% water-resistant and can be stored outside without damaging the quality of the tubes. The installation is in all weather conditions without problems possible. NEVOTUBE® formworks provide a perfect concrete surface. On columns up to 4 meters no visible, horizontal joints of the insert.

Cost-effectiveness

Fast and economical to use. Several columns can be poured in one working stage, guaranteeing optimum building progress on site. Extremely light and easy to handle during transport and erection. In the most of cases are no crane required on site. The columns can be stripped easily with a knife in seconds.

Eco-friendly

No cleaning and return of the formwork necessary. Requires no mould oils or release agents. Unproblematic waste disposal.

Dimension mm	Outside Ø mm	Chamfer approx. mm	Speed of casting m/h	Required amount of concrete approx. m³/m	Weight approx. kg/m
175x175	240	13	6	0,03	2,6
200x200	265	24	6	0,04	3,0
240x240	313	32	6	0,06	4,3
250x250	330	30	6	0,06	4,0
300x300	400	30	5	0,09	5,7
350x350	470	31	4	0,12	7,0
365x365	500	21	3	0,13	7,5
400x400	550	20	3	0,16	8,8
450x450	600	42	3	0,20	10,3
500x500	685	27	3	0,25	13,0

Perfect facing concrete! Other dimension available on request.

If self-compacting concrete is used, the casting speeds have to be halved.

