

## SCHALROHR NEVOTUBE® “6-ECK“

Spanner size “S” mm	Corner “E” mm	Leg length “A” mm	Outside Ø mm	Weigth approx. kg/m
250	288	144	394	3,7
300	346	173	452	4,4
350	404	202	510	5,1
400	462	231	567	6,3
500	578	289	682	7,4

Perfect facing concrete! Other dimensions available on request.

If self-compacting concrete is used, the casting speeds have to be halved.

## SCHALROHR NEVOTUBE® “8-ECK“

Spanner size “S” mm	Corner “E” mm	Leg length “A” mm	Outside Ø mm	Weigth approx. kg/m
250	270	104	376	3,5
300	325	125	430	4,2
350	379	145	484	4,8
400	433	166	538	6,0
500	541	207	646	7,0

Perfect facing concrete! Other dimensions available on request.

If self-compacting concrete is used, the casting speeds have to be halved.


## SCHALROHR NEVOTUBE® “WANDANSCHLUSSÄULE“

Dimension mm	Outside Ø mm	Speed of casting m/h	Required amount of con- crete approx. m <sup>3</sup> /m	Weigth approx. kg/m
200x200	310	6	0,04	3,6
240x240	370	6	0,06	4,4
250x250	380	6	0,06	4,5
300x300	460	5	0,09	5,1
350x350	530	4	0,12	5,9
400x400	600	3	0,16	6,8
450x450	670	3	0,20	7,9
500x500	745	3	0,25	8,7
200x250	352	6	0,05	4,4
200x300	395	6	0,06	5,0
200x350	435	6	0,07	5,7
200x400	478	5	0,07	6,5
200x500	582	4	0,10	7,6
250x300	425	5	0,08	5,3
250x350	463	5	0,08	6,2
250x400	508	4	0,10	6,6
250x500	600	3	0,13	7,7
300x350	495	4	0,11	7,0
300x400	534	3	0,12	7,6
300x500	620	3	0,15	8,7
350x400	562	3	0,14	8,2
350x500	645	3	0,18	9,6
400x500	673	3	0,20	10,4


Perfect facing concrete! Other dimensions available on request.

If self-compacting concrete is used, the casting speeds have to be halved.

Column formwork Nevotube®  
„Hexagon“



Column formwork Nevotube®  
„Oktagon“



Column formwork Nevotube®  
„for existing walls“

