

**TEST CERTIFICATION
ON REQUEST**

Vapour Barrier Sheets
white or blue

**PE-DAMPFBREMSFOLIE**

The PE vapour barrier film is a specially manufactured film with high vapour diffusion resistance. The PE-Dampfbremsfolie will be fixed inside of the building components to prevent an air change from inside and outside. A result is the prevention of creation of condensation.

| Item-No. | Strength mm | Width m | Length m | Quantity of coil | m ² /Pallet |
|----------|-------------|---------|----------|------------------|------------------------|
| FDB16... | 0,160 | 4 | 25 | 75 | 7.500 |
| FDB20... | 0,200 | 4 | 25 | 52 | 5.200 |
| FDB25... | 0,250 | 4 | 25 | 46 | 4.600 |
| FDB45... | 0,450 | 4 | 25 | 27 | 2.700 |

Other dimension (width/length) available on request.

- tested according DIN 13984
- fire classification E
- not permeable

**PE-BAUFOLIE - TRANSPARENT**

The transparent construction film is made of low-density 100% polyethylene. Transparent with no self-coloration.

PE-Construction Film
transparent



| Item-No. | Strength mm | Width m | Length m | Quantity of coil | m ² /Pallet |
|-----------|-------------|---------|----------|------------------|------------------------|
| FNS030... | 0,030 | 2 | 100 | 100 | 20.000 |
| FNS040... | 0,040 | 2 | 100 | 10 | 20.000 |
| FNS040... | 0,040 | 4 | 100 | 75 | 30.000 |
| FNS050... | 0,050 | 2 | 50 | 100 | 10.000 |
| FNS050... | 0,050 | 4 | 50 | 75 | 15.000 |
| FNS060... | 0,060 | 2 | 50 | 100 | 10.000 |
| FNS060... | 0,060 | 4 | 50 | 75 | 15.000 |
| FNS100... | 0,100 | 2 | 50 | 94 | 9.400 |
| FNS100... | 0,100 | 4 | 50 | 60 | 12.000 |
| FNS120... | 0,120 | 2 | 50 | 75 | 7.500 |
| FNS120... | 0,120 | 4 | 50 | 46 | 9.200 |
| FNS150... | 0,150 | 2 | 50 | 75 | 7.500 |
| FNS150... | 0,150 | 4 | 50 | 44 | 8.800 |
| FNS200... | 0,200 | 2 | 50 | 60 | 6.000 |
| FNS200... | 0,200 | 4 | 50 | 33 | 6.600 |
| FNS300... | 0,300 | 4 | 25 | 44 | 4.400 |
| FNS400... | 0,400 | 4 | 25 | 27 | 2.700 |
| FNS500... | 0,500 | 4 | 25 | 27 | 2.700 |

Other dimension (width/length) available on request.

