

## HORIZONTAL

Spacer „horizontal“



Item-No.	Concrete cover mm	For bar Ø mm	Pcs/ Bag	Pcs/ Big bag	Pcs/ Pallet
H10	10	4-16	1.000	8.000	40.000
H15	15	4-16	1.000	6.000	36.000
H20	20	4-16	500	4.000	32.000
H25	25	4-16	500	3.500	28.000
H30	30	4-16	250	2.500	25.000
H35	35	4-16	250	1.500	24.000
H40	40	4-16	250	1.250	25.000
H45	45	4-16	125	1.000	12.000
H50	50	4-16	125	1.000	12.000




## 4-FUSS

The 4-foot is a stable spacer with a large clamping range for middle and heavy reinforcement. Ideal for use in all areas of application in the precast industry and on construction sites.

Spacer „4-foot“



 ATVF - with flat foot spikes

 ATVS - with pointed foot spikes

Item-No.	Concrete cover mm	For bar Ø mm	Pcs/ Bag	Pcs/ Big bag	Pcs/ Pallet
ATV...20	20	6-20	500	2.000	12.000
ATV...25	25	6-20	500	1.500	12.000
ATV...30	30	6-20	250	1.500	12.000
ATV...35	35	6-20	250	1.000	10.000
ATV...40	40	6-20	250	1.000	10.000
ATV...45	45	6-20	250	1.000	8.000
ATV...50	50	6-20	125	500	7.500
ATV...55	55	6-20	125	500	7.500

Approved according to DBV specification „Abstandhalter“ DBV - c - A (ATVF = L2, ATVS = L1)



## MIT GRUNDPLATTE

Spacer „with baseplate“



Item-No.	Concrete cover mm	For bar Ø mm	Pcs/ Bag	Pcs/ Pallet
ATM1520	15 / 20	8-16	500	16.000
ATM2530	25 / 30	8-16	400	12.800
ATM4050	40 / 50	6-16	200	16.000
ATM5060	50 / 60	6-16	200	13.600
ATM7080	70 / 80	8-16	200	7.200
ATM90100	90 / 100	8-16	100	6.400

