

Productvideo



Formwork spacer



**Test certificates:**

- 1) Water leakage
- 2) Fire behaviour F180
- 3) Airborne sound insulation
- 4) Suitable for drinking water
- 5) Aggressive, chemical, polluted water

## OKTAGON®-PLUS 22

TEST CERTIFICATION  
ON REQUEST

Formwork spacer OKTAGON®-PLUS 22 for tie rod Ø 15/17mm.

| Item-No. | Wall thickness mm | Pcs/ Bag | Pcs/ Pallet |
|----------|-------------------|----------|-------------|
| *OP15    | 150               | 100      | 2.400       |
| OP175/3T | 175               | 100      | 2.400       |
| *OP18    | 180               | 100      | 2.400       |
| *OP20    | 200               | 100      | 2.400       |
| OP22/3T  | 220               | 100      | 2.400       |
| *OP24    | 240               | 100      | 2.400       |
| *OP25    | 250               | 100      | 2.400       |
| *OP30    | 300               | 100      | 2.400       |
| *OP35    | 350               | 100      | 1.500       |
| OP36/3T  | 360               | 100      | 1.500       |
| *OP365   | 365               | 100      | 1.500       |
| *OP40    | 400               | 100      | 1.500       |
| OP45/3T  | 450               | 50       | 800         |
| OP50/3T  | 500               | 50       | 800         |
| OP55/3T  | 550               | 50       | 800         |
| OP60/3T  | 600               | 50       | 800         |

\* made of one piece (free of PVC). Delivery incl. plugs.  
Other length available on request.



OKTAGON®-PLUS cone 22



## OKTAGON®-PLUS KONUS 22

OKTAGON®-PLUS cone 22 for creating waterproof formwork spacers. Custom made lengths can be made, by using an OKTAGON®-PLUS cone 22 and a 22/26 tube that has to be cut down 8cm less than the required wall thickness.

| Item-No. | For tube Ø mm | Pcs/ Bag | Pcs/ Pallet |
|----------|---------------|----------|-------------|
| OPK      | 22/26         | 200      | 5.000       |



OKTAGON® plug 22



## OKTAGON® STOPFEN 22

OKTAGON® plug 22 for waterproof sealing of OKTAGON®-PLUS cone 22. May only be hammered into place, no glue required!

| Item-No. | Pcs/ Bag | Pcs/ Pallet |
|----------|----------|-------------|
| OS       | 200      | 25.000      |



# OKTAGON®-PLUS 22 SICHTBETONSCHEIBE AUS GIESSBETON 22

**TEST CERTIFICATION  
ON REQUEST**

Special solution: Cast concrete plate. To be glued on the OKTAGON® plug. Shadow gap approx. 2mm.

| Item-No. | Pcs/Box | Pcs/Pallet |
|----------|---------|------------|
| OPS/GBS  | 100     | -          |

*Fair-faced concrete plate 22 made of cast concrete*



# OKTAGON®-PLUS SICHTBETONSTOPFEN 22

OKTAGON®-PLUS fair-faced concrete plug (plastic) for waterproof sealing of OKTAGON®-PLUS 22. May only be hammered into place, no glue required! The result is a small shadow gap.

| Item-No. | Pcs/Bag | Pcs/Pallet |
|----------|---------|------------|
| OPS/KS   | 200     | 25.000     |

*OKTAGON®-PLUS fair-faced concrete plug 22*



*Other colours of the OKTAGON®-PLUS fair-faced concrete plug 22 available on request.*



# OKTAGON®-PLUS SAMPLE BOX

