

Productvideo



Formwork spacer



Test certificates:

- 1) Water leakage
- 2) Fire behaviour F180
- 3) Airborne sound insulation
- 4) Suitable for drinking water
- 5) Aggressive, chemical, polluted water

OKTAGON®-PLUS 26

TEST CERTIFICATION
ON REQUEST

Formwork spacer OKTAGON®-PLUS 26 for tie rod Ø 20/23mm.

Item-No.	Wall thickness mm	Pcs/ Bag	Pcs/ Pallet
OP26/20/3T	200	100	2.400
OP26/24/3T	240	100	2.400
OP26/25/3T	250	100	2.400
OP26/30/3T	300	100	2.400
OP26/35/3T	350	100	1.500
OP26/40/3T	400	100	1.500
OP26/60/3T	600	50	800

Delivery incl. plugs.

Other length available on request.



OKTAGON®-PLUS cone 26



OKTAGON®-PLUS KONUS 26

OKTAGON®-PLUS cone 26 for creating waterproof formwork spacers. Custom made lengths can be made, by using an OKTAGON®-PLUS cone 26 and a 26/30 tube that has to be cut down 8cm less than the required wall thickness.

Item-No.	For tube Ø mm	Pcs/ Bag	Pcs/ Pallet
OPK26	26/30	200	6.000



OKTAGON® plug 26



OKTAGON® STOPFEN 26

OKTAGON® plug 26 for waterproof sealing of OKTAGON®-PLUS cone 26. May only be hammered into place, no glue required!

Item-No.	Pcs/ Bag	Pcs/ Pallet
OS26	200	25.000



DICHTSCHEIBE

EPDM sealing disc with self adhesive foil, fits for OKTAGON®-PLUS.



Item-No.	For item	Inside Ø mm	Outside Ø mm	Strength mm	Pcs/ Coil	Coil/ Box	Pcs/ Pallet
DISOP	OP22	25	42	6	250	9	22.500
DISOP26	OP26	27	45	6	250	9	22.500

