

MIT HOHLKEHLE

Item-No.	Concrete cover mm	Cut width mm	Depth of hollow mm	Width of hollow mm	Pcs/ Bag	Pcs/ Pallet
FBE2H20/30/10	20	30	10	12	250	8.000
FBE2H25/30/10	25	30	10	12	200	8.000
FBE2H30/30/10	30	30	10	12	200	8.000
FBE2H35/30/10	35	30	10	12	200	8.000
FBE2H40/30/10	40	30	10	12	200	8.000
FBE2H45/30/10	45	30	10	12	150	6.000
FBE2H50/30/10	50	30	10	12	150	6.000

For iron bar up to Ø 12mm.

Approved according to DBV specification „Abstandhalter“ DBV - c - L2/F/T/A

Fibre concrete spacer
„with groove“
with 2 hooks lengthwise



Item-No.	Concrete cover mm	Cut width mm	Depth of hollow mm	Width of hollow mm	Pcs/ Bag	Pcs/ Pallet
FBE2H20/40/10Q	20	40	10	12	200	6.000
FBE2H25/40/10Q	25	40	10	12	150	6.000
FBE2H30/40/10Q	30	40	10	12	150	6.000
FBE2H35/40/10Q	35	40	10	12	150	6.000
FBE2H40/40/10Q	40	40	10	12	150	6.000
FBE2H45/40/10Q	45	40	10	12	150	6.000
FBE2H50/40/10Q	50	40	10	12	125	5.000

For iron bar up to Ø 12mm.

Approved according to DBV specification „Abstandhalter“ DBV - c - L2/F/T/A

Fibre concrete spacer
„with groove“
with 2 hooks across



TUNNELABSTANDHALTER FASERBETON

Item-No.	Concrete cover mm	Dimension mm	Pcs/ Bag	Pcs/ Pallet
FBTU40D2	40	100x100	25	1.000
FBTU50D1	50	100x100	25	1.000

Optional with glued on geotextile for protection of the tunnel foil.

Dimension 80x80 or 80x100mm also possible.

Approved according to DBV specification „Abstandhalter“ DBV - c - L2/F/T/A

Fibre concrete tunnel spacer
„Faserbeton“
2x 1,4mm wire (black)



SCHLITZWANDABSTANDHALTER

Item-No.	Concrete cover mm	Length mm	Width mm	Slope	Pcs/ Pallet
FBVS50/250	50	150/250	50	45°	800
FBVS70/330	70	190/330	70	45°	300

Custom-made product. Other dimension available on request.

Approved according to DBV specification „Abstandhalter“ DBV - c - L2/F/T/A

Fibre concrete spacer
„Diaphragm“

