

## 3-PUNKT AUFLAGE


Item-No.	Concrete cover mm	For bar Ø mm	Pcs/Bag	Pcs/Pallet
GBVA20..	20	4-14	350	14.000
GBVA25..	25	4-14	325	13.000
GBVA30..	30	4-14	300	12.000
GBVA35..	35	4-14	250	10.000
GBVA40..	40	4-14	250	10.000
GBVA45..	45	4-14	200	8.000
GBVA50..	50	4-14	200	8.000
GBVA60..	60	4-14	115	4.600
GBVA70..	70	4-14	92	3.680

Approved according to DBV specification „Abstandhalter“ DBV - c - L2/F/T/A

Cast concrete single spacer  
„Three feet“



..KK - with plastic clamp  
..FB - with shuttlecock clip  
..O - with eye hook



## 4-PUNKT AUFLAGE

Item-No.	Concrete cover mm	For bar Ø mm	Pcs/Bag	Pcs/Pallet
GBVA15/4..	15	4-14	300	18.000
GBVA20/4..	20	4-14	300	18.000
GBVA25/4..	25	4-14	300	18.000
GBVA30/4..	30	4-14	250	13.750
GBVA35/4..	35	4-14	250	11.250
GBVA40/4..	40	4-14	250	10.000
GBVA50/4..	50	4-14	200	8.000

Approved according to DBV specification „Abstandhalter“ DBV - c - L2/F/T/A

Cast concrete single spacer  
„Four feet“



..KK - with plastic clamp  
..FB - with shuttlecock clip  
..O - with eye hook

