

HOHLWANDDÜBEL „K“

Double-wall dowel



Double-wall dowel HWD12 for temporary fixation push-pull props / precast element installation. For mounting of double- and massivwalls. The double-wall dowel is factory-positioned on the formwork with hot glue. Best possible hold by roughened adhesive surfaces with Ø 50mm. Small recess in the adhesive plate for minimal hot glue consumption. Alternative positioning of the cavity wall dowels on steel formwork tables, the adhesive plate can be factory-fixed with a klebepad (double-sided adhesive on carrier foil). Positive effect, there is no more hot glue in the screw guide! To fix the push-pull props on the double-wall dowel a wood screw DIN 571, Ø 12x70mm must be used. Due to a predetermined breaking point of the adhesive plate is easy to remove. Supplied without screw and washer.

Item-No.	Description	Pcs/Bag	Pcs/Pallet
HWD12	Double-wall dowel „K“ suitable for wood screw 12x70mm with adhesive plate	250	12.500



Double-wall dowel with magnet



HOHLWANDDÜBEL „M“

Double-wall dowel HWDM12 same application as HWD12. The HWDM12 is positioned on the steel formwork with the reusable magnet for cavity wall dowels. After stripping, the magnet usually remains on the formwork due to its high adhesive force. The HWDM12 is right positioned in the concrete element. To fix the push-pull props on the double-wall dowel a wood screw DIN 571, Ø 12x80mm must be used. Supplied without screw and washer. Order both items HWDM and HWDM12 required.

Item-No.	Description	Pcs/Bag	Pcs/Pallet
HWDM12	Double-wall dowel „M“ suitable for wood screw 12x80mm for magnet	250	12.500
HWDM	MAGNET for Double-wall dowel „M“	1	-



MAGNET for Double-wall dowel „M“ (Item-No. HWDM)



+

Double-wall dowel „M“ suitable for wood screw 12x80mm for magnet (Item-No. HWDM12)



=

HOHLWANDDÜBEL „M“

