

Double wall spacer
RAZZO 1



RAZZO 1

Spacer for prefabricated double walls. Efficient attachment by sliding shoe underneath the reinforcement. The spacer is in a safe position immediately.

Item-No.	Concrete cover mm	Wall thickness mm	Iron Ø mm	Pcs/Box	Pcs/Pallet
RAZ../180	15-50	180	8 or 10	150	3.000
RAZ../200	15-35	200	8 or 10	150	3.000
RAZ../240	15-35	240	8 or 10	150	3.000
RAZ../250	15-35	250	8 or 10	150	3.000
RAZ../300	15-35	300	8 or 10	150	3.000
RAZ../350	15-35	350	8 or 10	100	2.000
RAZ../400	15-35	400	8 or 10	100	2.000

Other length or wall thickness available on request.



Double wall spacer
RAZZO 2



RAZZO 2

Spacer for prefabricated double walls. Small foot for close-meshed reinforcement.

Item-No.	Concrete cover mm	Wall thickness mm	Iron Ø mm	Pcs/Box	Pcs/Pallet
RAZ../200	20-35	200	8 or 10	300	6.000
RAZ../240	20-35	240	8 or 10	250	5.000
RAZ../250	20-35	250	8 or 10	250	5.000
RAZ../300	20-35	300	8 or 10	200	4.000

Other length or wall thickness available on request.



Double wall spacer with steel core
RAZZO-PLUS (RAZS...)



RAZZO-PLUS & RAZZO-PRO MIT STAHLKERN

TEST CERTIFICATION ON REQUEST

Robust spacer for prefabricated double walls. Made of special plastic in one piece with steel core. Efficient attachment by sliding shoe underneath the reinforcement. The spacer is in a safe position immediately.

Item-No.	Concrete cover mm	Wall thickness mm	Iron Ø mm	Pcs/Box	Pcs/Pallet
*RAZS/180S	15-50	180	8	145	3.480
*RAZS/200S	15-50	200	8	125	3.000
*RAZS/240S	15-50	240	8	115	2.760
*RAZS/250S	15-50	250	8	105	2.520
*RAZS/300S	15-50	300	8	90	2.160
RAZP/350S	15-50	350	8	-	420
RAZP/400S	15-50	400	8	-	420

* also available RAZZO-PLUS WU (RAZS/...SQ) !



Double wall spacer with steel core
RAZZO-PRO (RAZP...)



RAZZO-PLUS WU

With active sealing ring against liquid entry. 5 Bar test pressure due to DIN EN 12390-8.

